



SD-80H



Simple Operation

Simple operation by ON/OFF switch

Strong Durability

Waterproof by silicon, strong ABS body

Strong Cleaning performance

Built in powerful BLT vibrator

Warming up mode

Keep up the temperature of liquid (65c).

Specification

Model	SD-80H	Consumption Wattage	0.65A
Inside Diameter	150(W)×135(L)×60(H)	Gross Weight	1.8 KG
Outside Diameter	177(W)×162(L)×168(H)	Power	AC220V / 60Hz
Capacity	1.2L	Operation Time	max. 5min heat-on temp. 65°C ±10%
Ultrasonic Frequency	40KHz	Materials	tub:SUS-304 body:ABS-GP22
Ultrasonic Output	50W	Parts	cover, fuse x 2, manual

Cleaning Liquid (for options)

Required for better cleaning performance

Model	11UN	16PLUS	1169
Component	Alkali	Neutrality	Alkali
Target	glass, quartz, ceramic ware, crystal compound, rubber, iron, metal	aluminum, zinc, tin, borosilicate, glass, quartz glass, stainless, chrome, nickel, polyethylene polypropylene, Teflon, silicon rubber, rubber	nonferrous metal, stainless, chrome steel, iron steel, precious metal, titanium, nickel
Solution rate	3/100%	3/100%	3/100%

SD-ULTRASONIC CO.,LTD

No.560, Sewoon B/D, #173 Jangsa-dong, Jongro-ku, Seoul, Korea
Tel] +82-1644-5897 Fax] +82-2-2278-2276
<http://www.sd-ultra.com>