



## SD-D250H



### *Digital Indicator*

Display setting value, Current value, operation time, output value.

### *Strong Durability & Cleaning performance*

waterproof by silicon, strong stainless body  
Built in powerful BLT vibrator

### *Ultrasonic Output Control*

Set the output of 5-100%.

### *Temperature mode*

Display the value of current / setting (30-80c).

### *Sweep Function*

Generate two different sequential frequencies to clean more widely/efficiently during ultrasonic operation

## Specification

Model	SD-D250H	Consumption Wattage	1.95A
Inside Diameter	290(W)×150(L)×150(H)	Gross Weight	6KG
Outside Diameter	350(W)×176(L)×300(H)	Power	AC220V / 60Hz
Capacity	6L	Operation Time	0-60min. heat-on temp. (30~80℃)±10%
Ultrasonic Frequency	40KHz	Materials	tub:SUS-304 body:SUS-430
Ultrasonic Output	150W	Parts	cover, fuse x 2, manual, BT250

## Cleaning Liquid (for options)

Required for better cleaning performance

Model	11UN	16PLUS	1169
Component	Alkali	Neutrality	Alkali
Target	glass, quartz, ceramic ware, crystal compound, rubber, iron, metal	aluminum, zinc, tin, borosilicate, glass, quartz glass, stainless, chrome, nickel, polyethylene polypropylene, Teflon, silicon rubber, rubber	nonferrous metal, stainless, chrome steel, iron steel, precious metal, titanium, nickel
Solution rate	3/100%	3/100%	3/100%

## SD-ULTRASONIC CO.,LTD

No.560, Sewoon B/D, #173 Jangsa-dong, Jongro-ku, Seoul, Korea  
Tel] +82-1644-5897 Fax] +82-2-2278-2276  
<http://www.sd-ultra.com>