

Ультразвукові ванни SD ULTRA



Compact Size
Ultrasonic cleaner

Analogue



SIMPLE OPERATION, STRONG DURABILITY, EXCELLENT CLEANING PERFORMANCE

Simple on/off switch, Waterproof by silicon, Strong ABS body, Built in powerful BLT vibrator



SD-80W



SD-80H



SD-100H



SD-120H

Inside dimension(mm)	150(W)×135(D)×60(H)	150(W)×135(D)×60(H)	150(W)×135(D)×60(H)	150(W)×135(D)×100(H)
Outside dimension(mm)	177(W)×162(D)×168(H)	177(W)×162(D)×168(H)	177(W)×162(D)×168(H)	177(W)×162(D)×211(H)
Capacity	1.2L	1.2L	1.2L	1.8L
Ultrasonic frequency	40kHz	40kHz	28kHz	28kHz
Ultrasonic output	50W	50W	50W	50W
Consumption wattage	120W	120W	140W	145W
Gross weight	1.4KG	1.5KG	1.7KG	2.3KG
Heat capacity	-	70W	70W	70W
Power	AC220V~230V / 50~60Hz	AC220V~230V / 50~60Hz	AC220V~230V / 50~60Hz	AC220V~230V / 50~60Hz
Operation time	Max. 5min.	-Max. 5min. -Thermostat : 65c +/-10%	-Max. 5min. -Thermostat : 65c +/-10%	-Ultrasonic operation : 0~30min. -Thermostat : 65c +/-10%
Materials	Tub SUS-304, Body ABS-GP22	Tub SUS-304, Body ABS-GP22	Tub SUS-304, Body ABS-GP22	Tub SUS-304, Body SUS-430

Analogue
Ultrasonic cleaner

Analogue



SIMPLE OPERATION, STRONG DURABILITY, EXCELLENT CLEANING PERFORMANCE

Simple on/off switch, Waterproof by silicon, Strong ABS body, Built in powerful BLT vibrator



SD-200H



SD-250H



SD-300H



SD-350H

Inside dimension(mm)	240(W)×140(D)×100(H)	290(W)×150(D)×150(H)	290(W)×240(D)×150(H)	500(W)×300(D)×150(H)
Outside dimension(mm)	298(W)×162(D)×250(H)	359(W)×176(D)×303(H)	393(W)×265(D)×307(H)	605(W)×325(D)×312(H)
Capacity	3.3L	6L	10L	22L
Ultrasonic frequency	40kHz	40kHz	40kHz	28kHz
Ultrasonic output	100W	150W	200W	300W
Consumption wattage	290W	340W	540W	760W
Gross weight	3.4KG	5.2KG	7KG	10.8KG
Heat capacity	140W	140W	210W	280W
Power	AC220V~230V / 50~60Hz	AC220V~230V / 50~60Hz	AC220V~230V / 50~60Hz	AC220V~230V / 50~60Hz
Operation time	-Ultrasonic operation : 0~30min. -Thermostat : 30~85c +/-10%	-Ultrasonic operation : 0~30min. -Thermostat : 30~85c +/-10%	-Ultrasonic operation : 0~30min. -Thermostat : 30~85c +/-10%	-Ultrasonic operation : 0~30min. -Thermostat : 30~85c +/-10%
Materials	Tub SUS-304, Body SUS-430	Tub SUS-304, Body SUS-430	Tub SUS-304, Body SUS-430	Tub SUS-304, Body SUS-430

Digital Type
Ultrasonic cleaner

Digital



DIGITAL INDICATOR, SIMPLE OPERATION, STRONG DURABILITY, EXCELLENT CLEANING PERFORMANCE

- Control the setting temperature, current temperature, ultrasonic operation's time and the ultrasonic output (20~100%)
- Simple of/off switch
- Waterproof by silicon, Strong durability
- Built in powerful BLT vibrator



SD-D250H



SD-D300H



SD-D400H

Inside dimension(mm)	290(W)×150(D)×150(H)	290(W)×240(D)×150(H)	500(W)×300(D)×150(H)
Outside dimension(mm)	359(W)×176(D)×303(H)	393(W)×265(D)×307(H)	605(W)×325(D)×312(H)
Capacity	6L	10L	22L
Ultrasonic frequency	40kHz	40kHz	40kHz
Ultrasonic output	150W	200W	400W
Consumption wattage	528W	695W	990W
Gross weight	5.8KG	8KG	12.9KG
Heat capacity	140W	210W	280W
Power	AC220V~230V / 50~60Hz	AC220V~230V / 50~60Hz	AC220V~230V / 50~60Hz
Operation time	-Ultrasonic operation : 0~60min. -Thermostat : 30~85c +/-10%	-Ultrasonic operation : 0~60min. -Thermostat : 30~85c +/-10%	-Ultrasonic operation : 0~60min. -Thermostat : 30~85c +/-10%
Materials	Tub SUS-304, Body SUS-430	Tub SUS-304, Body SUS-430	Tub SUS-304, Body SUS-430



Digital Separate Type
Ultrasonic cleaner

Digital



Digital function Time, frequency, sweep display, output control

Remote control function Control ultrasonic on/off by foot switch.

Strong durability Built in main body with SUS to prevent any corrosive solution of chemicals.

Excellent cleaning performance Built in the automatic operation mode to perform effectively according to the change of water level.



Vibration part



Oscillator part

Model	TANK Inside dimension (mm)(WxDxH)	TANK Outside dimension (mm)(WxDxH)	BASKET Inside dimension (mm)(WxDxH)	Ultrasonic frequency	Capacity	Interval	Ultrasonic output
SD-N600H	400×300×250	480×380×400	330×320×140	40KHz	30L	10×10	600W
SD-N900H	450×350×300	530×430×450	380×280×190	40KHz	47L	10×10	900W
SD-N1200H	500×400×300	580×480×450	430×330×190	40KHz	60L	10×10	1200W
SD-N1500H	550×450×300	630×530×450	480×380×190	40KHz	74L	10×10	1500W

Spare Parts (Liquid/Vibrator)

Cleaner & Basket & Vibrator

Cleaning liquid & Vibrator

Use the cleaning liquid for the better performance.



11 UNIVERAL



16PLUS



1169



Vibrator

Cleaning Liquid	Model	Component	Target	희석률	
	11UN	Alkali	Glass, Quartz ceramic ware, Crystal, Compound, Rubber, Porcelain, Iron metal	3/100%	
	16PLUS	Neutral PH	Aluminum, Zinc, Tin, Silicate acid, Glass, Quartz glass, Ceramic, Stainless, Crome, Nickel, Polyethylene, Polypropylene, Teflon, Silicon rubber, Rubber	3/100%	
	1169	Alkali	Nonferrous metal, Stainless, Chrome, Iron, Jewelry, Nickel	3/100%	
Vibrator	Model	Resonance frequency Khz(%)	Resonance max. ohm(Ω)	Capacity pF(%)	Max output
	4535-28n/b	28 ± 0.8	30	3,800 ± 10	70W
	4535-40n/b	40 ± 1.2	30	3,800 ± 10	70W
	6035-28n/b	28 ± 0.8	30	3,800 ± 10	80W

Use good quality parts to meet customers' satisfactions.
 Always remember when we first began
 and now ready to jump into one of the leading manufacturers
 Pride of our company confidence with advanced technology

BASKET ACCESSORY



Model	BT-120	BT-200	BT-250	BT-300	BT-350
Inside dimension (mm)(W×D×H)	120×105×65	215×115×65	274×123×96	262×206×93	452×263×93
Outside dimension (mm)(W×D×H)	147×127×88	230×130×90	261×137×143	276×220×140	466×277×140
Interval(mm)	13×13	13×13	13×13	13×13	13×13